



Deck Features

- Rear 45° approach angle
- Detachable roller wheels
- Easy access tie-down points
- Structural steel construction

DECK SPECIFICATIONS

OPTIONS	ALL DECK EXTENSIONS
FLOOR	1/8" DIAMOND PLATE
CROSS MEMBERS	CHANNEL ON 12" CENTERS
BULKHEAD	2" X 2" X 1/8" TUBING TUBULAR FRAME WORK
TIE-DOWN LOOPS	3 LOOPS PER SIDE
DIMENSIONS	58" WIDE X 8' 4" LONG

LIFT SYSTEM SPECIFICATIONS

OPTIONS	ALL SYSTEM ACCESSORIES
LIFT ARM	ELECTRIC POWERED HYDRAULIC
HOOK-UP	PATENTED T-BAR LIFT ARM
CAPACITY	UP TO 2,500lbs (1,134kg)
BED LENGTHS	6.5' (78") 8' (96")

Specifications are subject to change with or without notice. Products not warranted for any specific purpose.

BUILT FOR AmeriDeck

System Features

- High quality powder coated finish
- Easy deck disconnect pins
- Easy to operate 2-way control pendant
- Adjustable deck feet





Deck Features

- Detachable roller wheels
- 2-way dump/ramp gate
- Sloped sides for easy clean out
- Angle sides with board pockets
- Structural steel construction

DECK SPECIFICATIONS

OPTIONS	NO DECK EXTENSIONS
FLOOR	1/8" STEEL SHEETING
CROSS MEMBERS	CHANNEL ON 12" CENTERS
BULKHEAD	2" X 2" X 1/8" TUBING TUBULAR FRAME WORK
STAKE POCKETS	24" ON CENTER
DIMENSIONS	58" WIDE X 8' 4" LONG

LIFT SYSTEM SPECIFICATIONS

OPTIONS	ALL SYSTEM ACCESSORIES
LIFT ARM	ELECTRIC POWERED HYDRAULIC
HOOK-UP	PATENTED T-BAR LIFT ARM
CAPACITY	UP TO 2,500lbs (1,134kg)
BED LENGTHS	6.5' (78") 8' (96")

Specifications are subject to change with or without notice. Products not warranted for any specific purpose.

BUILT FOR AmeriDeck

System Features

- High quality powder coated finish
- Easy deck disconnect pins
- Easy to operate 2-way control pendant
- Adjustable deck feet

